

View Online at <https://aerobasegroup.com/nsn/5306-01-335-2897>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.016 inches and 1.066 inches

**Fastener Length:**

Between 3.776 inches and 3.806 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.375 inches and 0.390 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Washer Quantity:**

1

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.750 inches

**Features Provided:**

Spacer

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c fastener and 40.0 rockwell c fastener

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.514 inches first hole and 3.564 inches first hole

**Primary Washer Outside Diameter:**

1.250 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

0.062 inches

**Material:**

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 6150 fastener or steel comp 8735 fastener or steel comp 8740 fastener

**Material Specification:**

Fed 66 federal standard all material responses primary washer

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2, cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0