

View Online at <https://aerobasegroup.com/nsn/5306-01-335-2897>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.016 inches and 1.066 inches

Fastener Length:

Between 3.776 inches and 3.806 inches

Head Style:

Dished hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Washer Quantity:

1

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Features Provided:

Spacer

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c fastener and 40.0 rockwell c fastener

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.514 inches first hole and 3.564 inches first hole

Primary Washer Outside Diameter:

1.250 inches

Primary Washer Style:

Flat

Primary Washer Material Thickness:

0.062 inches

Material:

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 6150 fastener or steel comp 8735 fastener or steel comp 8740 fastener

Material Specification:

Fed 66 federal standard all material responses primary washer

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0