

View Online at <https://aerobasegroup.com/nsn/5306-01-335-2906>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.666 inches

**Fastener Length:**

Between 1.221 inches and 1.251 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.327 inches and 0.347 inches

**Extended Washer Diameter:**

0.696 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Head Minor Diameter:**

Between 0.423 inches and 0.438 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.3750 inches

**Grip Length:**

Between 0.552 inches and 0.572 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Hole Configuration Style:**

Spline

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Hole drilled in top center of head, 0.230/0.270 in. Diameter x 0.108 in. Nomdeep

**Material:**

Steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837, type ii, class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.