NSN 5306-01-335-2906



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-335-2906 **Thread Class:**

За **Thread Direction:** Right-hand Thread Length: 0.666 inches **Fastener Length:** Between 1.221 inches and 1.251 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** 0.696 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Head Minor Diameter:** Between 0.423 inches and 0.438 inches **End Application:** Pacer dawn **Thread Diameter:** 0.3750 inches **Grip Length:** Between 0.552 inches and 0.572 inches **Hole Quantity:** 4 **Hole Type:** Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Hole Configuration Style:** Spline

Surface Finish:

32.0 microinches grip

Special Features:

Hole drilled in top center of head, 0.230/0.270 in. Diameter x 0.108 in. Nomdeep

NSN 5306-01-335-2906

Close Tolerance Bolt - Page 2 of 2



Material:
Steel
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837, type ii, class 2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):
Mil-c-8837 spec.