

View Online at <https://aerobasegroup.com/nsn/5306-01-335-2907>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.756 inches

Fastener Length:

Between 2.701 inches and 2.731 inches

Head Style:

Spline extended washer

Head Height:

Between 0.383 inches and 0.403 inches

Extended Washer Diameter:

0.812 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Head Minor Diameter:

Between 0.485 inches and 0.500 inches

End Application:

Pacer dawn

Thread Diameter:

0.4375 inches

Grip Length:

Between 1.928 inches and 1.948 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Spline

Surface Finish:

32.0 microinches grip

Special Features:

Hole drilled in top center of head, 0.290/0.330 in. Diameter x 0.125 in. Nomdeep

Material:

Steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.