

View Online at <https://aerobasegroup.com/nsn/5306-01-335-2908>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.844 inches

**Fastener Length:**

Between 2.025 inches and 2.055 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.440 inches and 0.460 inches

**Extended Washer Diameter:**

0.927 inches

**Extended Washer Thickness:**

Between 0.062 inches and 0.082 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Head Minor Diameter:**

Between 0.547 inches and 0.562 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.5000 inches

**Grip Length:**

Between 1.178 inches and 1.198 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Hole Configuration Style:**

Spline

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Hole drilled in top center of head, 0.350/0.390 in. Diameter x 0.144 in. Nomdeep

**Material:**

Steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837, type ii, class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.