NSN 5306-01-335-2908

Close Tolerance Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-335-2908

ou
Thread Direction:
Right-hand
Thread Length:
0.844 inches
Fastener Length:
Between 2.025 inches and 2.055 inches
Head Style:
Spline extended washer
Head Height:
Between 0.440 inches and 0.460 inches
Extended Washer Diameter:
0.927 inches
Extended Washer Thickness:
Between 0.062 inches and 0.082 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Head Minor Diameter:
Between 0.547 inches and 0.562 inches
End Application:
Pacer dawn
Thread Diameter:
0.5000 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Spline
Surface Finish:
32.0 microinches grip

Hole drilled in top center of head, 0.350/0.390 in. Diameter x 0.144 in. Nomdeep

Special Features:

NSN 5306-01-335-2908

Close Tolerance Bolt - Page 2 of 2



Material:
Steel
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837, type ii, class 2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):
Mil-c-8837 spec.