

View Online at <https://aerobasegroup.com/nsn/5306-01-335-2909>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.012 inches

**Fastener Length:**

Between 3.005 inches and 3.035 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.552 inches and 0.572 inches

**Extended Washer Diameter:**

1.158 inches

**Extended Washer Thickness:**

Between 0.080 inches and 0.100 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Head Minor Diameter:**

Between 0.673 inches and 0.688 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.6250 inches

**Grip Length:**

Between 1.985 inches and 2.015 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Hole Configuration Style:**

Spline

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Hole drilled in top center of head, 0.470/0.510 in. Diameter x 0.180 in. Nomdeep

**Material:**

Steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837, type ii, class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.