

View Online at <https://aerobasegroup.com/nsn/5306-01-335-2912>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.412 inches

Fastener Length:

Between 0.783 inches and 0.813 inches

Head Style:

Spline extended washer

Head Height:

Between 0.195 inches and 0.215 inches

Extended Washer Diameter:

0.354 inches

Extended Washer Thickness:

Between 0.017 inches and 0.037 inches

Hole Diameter:

Between 0.032 inches and 0.042 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Head Minor Diameter:

Between 0.173 inches and 0.188 inches

End Application:

Pacer dawn

Thread Diameter:

0.1900 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Spline

Surface Finish:

32.0 microinches grip

Special Features:

Hole drilled in top center of head, 0.070/0.110 in. Diameter x 0.088 in. Nomdeep

Material:

Steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type ii, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.