

View Online at <https://aerobasegroup.com/nsn/5306-01-335-4880>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.429 inches and 0.479 inches

Fastener Length:

Between 0.814 inches and 0.844 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Hole Diameter:

Between 0.070 inches and 0.080 inches

Locking Feature:

Patch threads

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Surface Finish:

32.0 microinches threads

Material:

Plastic polyamide locking feature

Material Specification:

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6306 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0