NSN 5306-01-335-7061

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-335-7061

Thread Class:
3a —
Thread Direction:
Right-hand
Thread Length:
0.323 inches
Fastener Length:
Between 0.933 inches and 0.963 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Locking Feature:
Patch threads or strip threads or pellet threads
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400 fastener
Material Specification:
Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener
Thread Series Designator:
Unjf

NSN 5306-01-335-7061

Shear Bolt - Page 2 of 2



Specification Data	a
--------------------	---

80205-nas6403 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0