

View Online at <https://aerobasegroup.com/nsn/5306-01-335-7061>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.323 inches

**Fastener Length:**

Between 0.933 inches and 0.963 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Hole Diameter:**

Between 0.046 inches and 0.056 inches

**Locking Feature:**

Patch threads or strip threads or pellet threads

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.615 inches and 0.635 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Hexagon corners

**Surface Finish:**

32.0 microinches threads

**Material:**

Titanium alloy uns r56400 fastener

**Material Specification:**

Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6403 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0