NSN 5306-01-335-7065

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-335-7065

View Online at https://aerobasegroup.com/nsn/5306-01-335-7
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.513 inches and 0.563 inches
Fastener Length:
Between 1.711 inches and 1.741 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.051 inches and 0.071 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Head Minor Diameter:
Between 0.383 inches and 0.389 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif
Shelf Life:
N/a

N/a

NSN 5306-01-335-7065

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0