## NSN 5306-01-336-0050

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-336-0050

view Online at https://aerobasegroup.com/hsh/3300-01-330-0
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.513 inches and 0.563 inches
Fastener Length:
Between 1.461 inches and 1.491 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.051 inches and 0.071 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Head Minor Diameter:
Between 0.383 inches and 0.389 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-336-0050

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0