Externally Relieved Body Bolt - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-01-336-6303

Inread Class: 3a Thread Inection: Right-hand Thread Length: Between 0.261 inches and 0.281 inches Fastener Length: Between 0.451 inches and 0.281 inches Head Style: Hexagon Head Height: Between 0.152 inches and 0.185 inches Width Between 0.152 inches and 0.185 inches Between 0.152 inches and 0.185 inches Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.502 inches First Diameter From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.374 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thread Vy Per Inch (tpi): 24 Esternally Relieved Body Diameter Quantity: 1 Special Features: Dry fin lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) asm standard single material response Thread Series Designator: Unjf Sheff Lite: Na Huit Of Measure: - Deministration: Na Fig: A003b0	
Thread Direction: Right-hand Thread Length: Between 0.261 inches and 0.281 inches Fastener Length: Between 1.635 inches and 1.655 inches Head Style: Head Style: Head Style: Between 0.152 inches and 0.185 inches Width Between Flats: Between 0.182 inches and 0.185 inches Width Between Flats: Between 0.374 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Destween 1.280 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thread Quty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Specification: Na Unif S	Thread Class:
Right-hand Thread Length: Between 0.261 inches and 0.281 inches Fastener Length: Between 1.635 inches and 1.655 inches Head Siyle: Head Siyle: Head Height: Between 0.152 inches and 0.185 inches Width Between Flats: Between 0.494 inches and 0.502 inches Width Between Flats: Between 0.374 inches and 0.502 inches Distance From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Destween 1.280 inches and 1.280 inches Pacer dawn Thread Diameter: 0.3750 inches Thread Diameter: 0.3750 inches Thread Steleved Body Diameter Quantity: 1 Stel comp h11 Material: Stel comp h11 Material Specification: Ams 6437 (h-11) assn standard single material response Thread Series Designator: Unjf Sheff Life: N/a Denilitarization: Na <tr td=""> Thread Series Designato:</tr>	
Tread Length: Between 0.261 inches and 0.281 inches Fastener Length: Between 1.635 inches and 1.655 inches Head Style: Head Aught: Between 0.152 inches and 0.185 inches Width Between Flats: Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches Pacer dawn Thread Unght: 24 Pacer dawn Thread Diameter: 0.3750 inches Pacer dawn Thread Diameter: 0.3750 inches Thread Jung Per Inch (tpi): 24 Stel comp h11 Materiai: Stel comp h11 Materiai: Stel comp h11 Materiai: Vai Unif Shell Comp h11 Materiai: Na Hot Of Measure: Image: Image:	
Between 0.281 inches and 0.281 inches Fastener Length: Between 1.635 inches and 1.655 inches Head Style: Head Style: Head Reight: Between 0.152 inches and 0.185 inches Width Between Flats: Between 0.374 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches Pacer dawn Thread Diameter: 0.3750 inches Stele comp h11 Material: Stele comp h11 Material: Viat Intred Specification: Na Unif Shell Ittle: Na Ittof Measure: Na	
Pastener Length: Between 1.635 inches and 1.655 inches Head Style: Hexagon Head Height: Between 0.152 inches and 0.185 inches With Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches Pacer dawn Thread Diameter: 0.3750 inches Thready Oty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shell Irie: Na Unit Of Measure: - Demilitarization: Na Here Series Designator: Here Series Designator: Na Diries Na	-
Between 1.635 inches and 1.655 inches Head Style: Hexagon Head Height: Between 0.152 inches and 0.185 inches With Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches Pacer dawn Thread Diameter: 0.3750 inches Thready Oxy Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designato: Unif Shel file: Na Unit Of Measure: - Presson: Na Panilitarization: Na Sheif I file: Na File: Na Sheif I file: <td></td>	
Head Style: Hexagon Head Height: Between 0.152 inches and 0.185 inches With Between Flats: Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Diatace From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thready Ry Per Inch (tpi): 24 Special Features: 0.3750 inches Thready Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ansel 7 (h-11) assn standard single material response Thread Specification: Na Unif Shelf Life: Na Did Measure: Thready Specification: Na Did Measure: Na	-
Hexagon Head Height: Between 0.152 inches and 0.185 inches Width Between Flats: Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designato:: Unif Shel Life: Na Unit Of Measure: - Pamilitarization: No Fig:	
Head Height: Between 0.152 inches and 0.185 inches Width Between Flats: Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thread Diameter: 0.3750 inches Thread Paleveed Body Diameter Quantity: 24 Steinerally Relieved Body Diameter Quantity: 1 Stei Comp h11 Material: Stei Comp h11 Material: Chread Seies Designator: Unif Shelf Life: N/a Dix Of Measure: - Dix Of Measure: - Pale Dix Of Measure: N/a Dix Of Measure: - Dix Of Measure: - Dix Of Measure: - Dix Of Measure:<	-
Between 0.152 inches and 0.185 inches Width Between Flats: Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube ong ping area only Material: Steel comp h11 Material: Shelf (h-11) assn standard single material response Thread Specification: N/a Unif Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Width Between Flats:Between 0.494 inches and 0.502 inchesFirst Diameter From Head:Between 0.374 inches and 0.376 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.260 inches and 1.280 inchesEnd Application:Pacer dawnThread Diameter:0.3750 inchesThready Qty Per Inch (tpi):24Special Features:Dry film lube on grip area onlyMaterial:Steel comp h11Material:Steel comp h11Material:UnjfShelf Life:NaNaFured Series Designator:UnjfShelf Life:NaNaFured Series Designator:NaShelf Life:NaFured Series Designator:NaFured Series Designator:NaFured Series Designator:NaFured Series Designator:Fured Series Designator:NaFured Series Designator:NaFured Series Designator:NaSteel Complex Series Designator:NaSteel Complex Series Designator:NaFured Series Designator:NaFured Series Designator:Fured Series Designator:	-
Between 0.494 inches and 0.502 inches First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thread Valy Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Steel Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Unif Sheff Life: N/a Unif Direct Subsignator: Unif Sheff Life: N/a Unit Of Measure: - Demilitarization: No	
First Diameter From Head: Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Steelal Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Between 0.374 inches and 0.376 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:Between 1.260 inches and 1.280 inchesEnd Application:Pacer dawnThread Diameter:0.3750 inchesThready Qty Per Inch (tpi):24Externally Relieved Body Diameter Quantity:1Special Features:Dry film lube on grip area onlyMaterial:Steel comp h11Material Specification:Ams 6487 (h-11) assn standard single material responseThread Series Designator:UnifSheff Life:N/aDrit of Measure:Panel Life:NaFig:	
Between 1.260 inches and 1.280 inches End Application: Pacer dawn Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Arns 6487 (h-11) assn standard single material response Thread Series Designator: Unif Sheft Life: N/a Drit of Measure: - Panellitarization: No Fig:	
End Application:Pacer dawnThread Diameter:0.3750 inchesThready Qty Per Inch (tpi):24Externally Relieved Body Diameter Quantity:1Special Features:Dry film lube on grip area onlyMaterial:Steel comp h11Material Specification:Thread Series Designator:UnifShelf Life:N/aInti Of Measure:TFinal FullFinal Specification:Shelf Life:N/aFinal Specification:Shelf Life:N/aFinal Specification:Shelf Life:N/aFinal Specification:Shelf Life:Shelf Life:She	
Pacer dawn Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Demilitarization: No	
0.3750 inches Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Arms 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thready Qty Per Inch (tpi): 24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
24 Externally Relieved Body Diameter Quantity: 1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unif Shelf Life: Na Dit of Measure: Fig:	
Externally Relieved Body Diameter Quantity:11Special Features:Dry film lube on grip area onlyMaterial:Steel comp h11Material Specification:Ams 6487 (h-11) assn standard single material responseThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
1 Special Features: Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Special Features:Dry film lube on grip area onlyMaterial:Steel comp h11Material Specification:Ams 6487 (h-11) assn standard single material responseThread Series Designator:UnifShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Externally Relieved Body Diameter Quantity:
Dry film lube on grip area only Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: Penilitarization: No Fig:	
Material: Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Steel comp h11 Material Specification: Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Femilitarization: No Fig:	
Material Specification:Ams 6487 (h-11) assn standard single material responseThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Ams 6487 (h-11) assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
-	
A003b0	-
	A003b0