

View Online at <https://aerobasegroup.com/nsn/5306-01-336-6304>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.276 inches and 0.296 inches

**Fastener Length:**

3.050 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.131 inches and 0.141 inches

**Width Between Flats:**

Between 0.430 inches and 0.440 inches

**First Diameter From Head:**

Between 0.312 inches and 0.313 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 2.690 inches and 2.700 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.2500 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Dry film lube on grip area only

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 (h-11) assn standard single material response

**Surface Treatment:**

Cadmium head

**Surface Treatment Specification:**

Nas 672 national specification single treatment response threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0