

View Online at <https://aerobasegroup.com/nsn/5306-01-336-6306>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.3750 inches

**Fastener Length:**

Between 1.870 inches and 1.890 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.194 inches and 0.204 inches

**Width Between Flats:**

Between 0.553 inches and 0.563 inches

**First Diameter From Head:**

Between 0.436 inches and 0.437 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

1.450 inches

**End Application:**

Pacer dawn

**Thread Diameter:**

0.3750 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Lubrication dry film lube per mil-I-46010, grip only

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium headcadmium threads

**Surface Treatment Specification:**

Nas 672 national specification single treatment response headnas 672 national specification single treatment response threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0