# NSN 5306-01-336-6318

Close Tolerance Bolt - Page 1 of 2





# **Thread Class:** 3a

**Thread Direction:** 

Right-hand

#### Thread Length:

Between 0.454 inches and 0.570 inches

#### Fastener Length:

Between 2.189 inches and 2.219 inches

#### Head Style:

Spline drive shear head

#### Head Height:

0.210 inches

Grip Diameter:

Between 0.373 inches and 0.374 inches

#### Head Minor Diameter:

#### 0.679 inches

End Application:

Pacer dawn

#### **Thread Diameter:**

0.3750 inches

#### Grip Length:

Between 1.740 inches and 1.760 inches

#### Thready Qty Per Inch (tpi):

24

#### **Special Features:**

Dry film lube on bearing surface of head: hole drilled in shank, 0.106 in. Diameter x 0.373/0.374 in. Nom deep

#### Material:

Steel comp h11

#### **Material Specification:**

Ams-6487 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Nas672 national specification single treatment response

### **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5306-01-336-6318

Close Tolerance Bolt - Page 2 of 2

Fiig: A003b0

