NSN 5306-01-336-6832

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-336-6832

Thread Class.
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.786 inches
Fastener Length:
3.036 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Head Minor Diameter:
Between 0.448 inches and 0.455 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 2.240 inches and 2.260 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches grip
Special Features:
Countersunk hole drilled 0.230 in. Min, 0.280 in. Maximum dia; 0.224 in. Lg from end
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5306-01-336-6832

Shear Bolt - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0