## NSN 5306-01-336-6834

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-336-6834

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.719 inches
Fastener Length:
1.844 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.383 inches and 0.389 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches grip
Special Features:
Countersunk hole end of shank 0.185 in. Min, 0.225 in. Maximum dia. 0.187 in. Lg from end
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-336-6834

Shear Bolt - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0