Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-336-7536

| Thread Clas   | SS:   |
|---------------|---|
| 3a            |   |
| Thread Dire   | action:   |
| Right-hand    |   |
| Thread Len    | gth:  |
| 0.426 inches  | 5   |
| Fastener Le   | ength:  |
| Between 1.3   | 302 inches and 1.332 inches   |
| Head Style:   |   |
| Flat counter  | sunk  |
| Head Diame    | eter:   |
| Between 0.3   | 360 inches and 0.381 inches   |
| Locking Fe    |   |
| Detent ball h |   |
| Thread Dia    |   |
| 0.190 inches  | 5   |
| Grip Lengtł   |   |
|               | 375 inches and 0.891 inches   |
|               | y Per Inch (tpi):   |
| 32            |   |
| Countersin    |   |
| 100.0 degre   |   |
| Surface Fin   |   |
| 32.0 microin  |   |
| Special Fea   |   |
|               | ith plunger and pawl ams 5629; ball qq-s-763 comp 440c  |
| Material:     |   |
|               | eel spring or cobalt alloy spring   |
|               | ecification:  |
|               | ssn standard single material response fastener or ams 4967 assn standard single material response fastene |
|               | ies Designator:   |
| Unjf          |   |
| Shelf Life:   |   |
| N/a           |   |
| Unit Of Mea   | asure:  |
|               |   |
| Demilitariza  | ation:  |
| No            |   |
| Fiig:         |   |
| A003b0        |   |