## NSN 5306-01-337-0352

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-337-0352

View Online at https://aerobasegroup.com/nsn/5306-01-337-0
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.755 inches and 0.805 inches
Fastener Length:
Between 2.015 inches and 2.045 inches
Head Style:
Spline extended washer
Head Height:
Between 0.440 inches and 0.460 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
Between 0.092 inches and 0.112 inches
Grip Diameter:
Between 0.4990 inches and 0.4995 inches
Head Minor Diameter:
Between 0.644 inches and 0.651 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

N/a

## NSN 5306-01-337-0352

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0