

View Online at <https://aerobasegroup.com/nsn/5306-01-337-5940>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.821 inches and 0.871 inches

Fastener Length:

Between 2.081 inches and 2.111 inches

Head Style:

Spline extended washer

Head Height:

Between 0.495 inches and 0.515 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.102 inches and 0.122 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Head Minor Diameter:

Between 0.711 inches and 0.717 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0