Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-337-6964

| Thread Clas | SS: |
|--------------|---|
| 2a | |
| Thread Dire | ection: |
| Right-hand | |
| Thread Len | igth: |
| 0.250 inches | |
| Fastener Le | ength: |
| | 594 inches and 0.656 inches |
| Head Style: | |
| Hexagon | |
| Head Heigh | it: |
| Between 0.0 | 067 inches and 0.080 inches |
| Width Betw | veen Flats: |
| Between 0.2 | 244 inches and 0.250 inches |
| First Diame | eter From Head: |
| 0.095 inches | S |
| Distance Fr | rom Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.3 | 344 inches and 0.406 inches |
| Thread Diar | meter: |
| 0.138 inches | S |
| Thready Qt | y Per Inch (tpi): |
| 32 | |
| Externally F | Relieved Body Diameter Quantity: |
| 1 | |
| Material: | |
| Steel comp 3 | 302 |
| Material Sp | ecification: |
| Qq-s-766 fe | deral specification single material response |
| Surface Tre | atment: |
| Passivate | |
| Surface Tre | eatment Specification: |
| Astma380 a | ssn standard single treatment response |
| Thread Seri | ies Designator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Mea | asure: |
| | |
| Demilitariza | ation: |
| No | |
| Fiig: | |
| A003b0 | |