## NSN 5306-01-337-9107

Shear Bolt - Page 1 of 2



AeroBase Group

| Thread Class:  |
|--|
| За   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.840 inches   |
| Fastener Length:   |
| Between 2.075 inches and 2.105 inches  |
| Head Style:  |
| Double hexagon w/hole  |
| Head Height:   |
| Between 0.470 inches and 0.490 inches  |
| Width Between Flats:   |
| Between 0.625 inches and 0.640 inches  |
| Extended Washer Diameter:  |
| Between 0.928 inches and 0.938 inches  |
| Extended Washer Thickness:   |
| Between 0.128 inches and 0.138 inches  |
| Grip Diameter:   |
| Between 0.5610 inches and 0.5615 inches  |
| Thread Diameter:   |
| 0.562 inches   |
| Grip Length:   |
| Between 1.240 inches and 1.260 inches  |
| Features Provided:   |
| Cetyl alcohol lubricant  |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Surface Finish:  |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads            |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams4967 assn standard single material response or ams4928 assn standard single material response |
| Surface Treatment:   |
| Phosphate  |
| Surface Treatment Specification:   |
|  |

Bac 5861 cagec 81205 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## NSN 5306-01-337-9107

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

