## NSN 5306-01-338-0401

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-338-0401

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.910 inches
Fastener Length:
Between 2.645 inches and 2.675 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.470 inches and 0.490 inches
Width Between Flats:
Between 0.616 inches and 0.627 inches
Extended Washer Diameter:
Between 0.928 inches and 0.938 inches
Extended Washer Thickness:
Between 0.123 inches and 0.143 inches
Grip Diameter:
Between 0.5605 inches and 0.5615 inches
Thread Diameter:
0.562 inches
Grip Length:
Between 1.740 inches and 1.760 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-338-0401

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0