NSN 5306-01-338-2827

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-338-2827

View Online at https://aerobasegroup.com/nsn/5306-01-338-2827
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:
Between 0.917 inches and 0.947 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum

NSN 5306-01-338-2827

Shear Bolt - Page 2 of 2



Surface	Treatment	t Specification:	

Nas 4006 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6404 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0