

View Online at <https://aerobasegroup.com/nsn/5306-01-338-3124>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.910 inches

Fastener Length:

Between 4.520 inches and 4.550 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.470 inches and 0.490 inches

Width Between Flats:

Between 0.616 inches and 0.627 inches

Extended Washer Diameter:

Between 0.929 inches and 0.938 inches

Extended Washer Thickness:

Between 0.123 inches and 0.143 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

End Application:

Ea-6b prowlair aircraft, a-6e intruder aircraft

Thread Diameter:

0.562 inches

Grip Length:

Between 3.615 inches and 3.635 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Bms10-85, cagec 81205 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0