

View Online at <https://aerobasegroup.com/nsn/5306-01-338-3124>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.910 inches

**Fastener Length:**

Between 4.520 inches and 4.550 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.470 inches and 0.490 inches

**Width Between Flats:**

Between 0.616 inches and 0.627 inches

**Extended Washer Diameter:**

Between 0.929 inches and 0.938 inches

**Extended Washer Thickness:**

Between 0.123 inches and 0.143 inches

**Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

**End Application:**

Ea-6b prowler aircraft, a-6e intruder aircraft

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 3.615 inches and 3.635 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Bms10-85, cagec 81205 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0