## **NSN 5306-01-338-3340** Shear Bolt - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5306-01-338-3340
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.531 inches
Fastener Length:
Between 1.204 inches and 1.234 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Head Minor Diameter:
Between 0.383 inches and 0.389 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Гhready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Special Features:
Threaded hole in top of head 0.138-32 unjc-3b. Injection port 0.120 in. Lg; 0.060 in. Wide in unthd shank; distance from head to beginning
of injection port 0.100 in. Lg
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Jnjf
Sholf Life:

## NSN 5306-01-338-3340

Shear Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0