

View Online at <https://aerobasegroup.com/nsn/5306-01-338-5605>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.250 inches and 1.781 inches

**Fastener Length:**

Between 1.734 inches and 1.781 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.368 inches and 0.375 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.550 inches and 0.562 inches

**Extended Washer Thickness:**

Between 0.115 inches and 0.135 inches

**Locking Feature:**

Patch threads or strip threads or pellet threads

**Thread Diameter:**

0.375 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c fastener and 45.0 rockwell c fastener

**Material:**

Plastic polyamide locking feature steel fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416, ty2 cl3 federal specification single treatment response fastener

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0