NSN 5306-01-338-5605

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-338-5605 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.250 inches and 1.781 inches **Fastener Length:** Between 1.734 inches and 1.781 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.368 inches and 0.375 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.550 inches and 0.562 inches **Extended Washer Thickness:** Between 0.115 inches and 0.135 inches **Locking Feature:** Patch threads or strip threads or pellet threads **Thread Diameter:** 0.375 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c fastener and 45.0 rockwell c fastener Material: Plastic polyamide locking featuresteel fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, ty2 cl3 federal specification single treatment response fastener **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-01-338-5605

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0