## NSN 5306-01-338-6329



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-338-6329 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.608 inches **Fastener Length:** Between 0.968 inches and 0.998 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** 

Between 0.044 inches and 0.064 inches

**Hole Diameter:** 

Between 0.050 inches and 0.060 inches

**Grip Diameter:** 

Between 0.3740 inches and 0.3745 inches

**Head Minor Diameter:** 

Between 0.448 inches and 0.455 inches

**Thread Diameter:** 

0.375 inches

**Grip Length:** 

Between 0.365 inches and 0.385 inches

**Hole Quantity:** 

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

220000 pounds per square inch

**Hole Configuration Style:** 

Spline

**Surface Finish:** 

32.0 microinches fastener

Material:

Nickel alloy 718

**Material Specification:** 

Ams 5662 assn standard single material response

## NSN 5306-01-338-6329

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiin.