

View Online at <https://aerobasegroup.com/nsn/5306-01-338-7281>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.469 inches

Fastener Length:

Between 0.766 inches and 0.796 inches

Head Style:

Spline extended washer

Head Height:

Between 0.240 inches and 0.260 inches

Extended Washer Diameter:

Between 0.460 inches and 0.470 inches

Extended Washer Thickness:

Between 0.026 inches and 0.046 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Head Minor Diameter:

Between 0.297 inches and 0.312 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Special Features:

Threaded hole in top of head 0.138-32 unjc-3b. Injection port 0.120 in. Lg; 0.060 in. Wide in unthd shank; distance from head to beginning of injection port 0.070 in. Lg.

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0