

View Online at <https://aerobasegroup.com/nsn/5306-01-338-7285>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.643 inches

**Fastener Length:**

Between 1.128 inches and 1.158 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.330 inches and 0.350 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0