## NSN 5306-01-338-7285

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-338-7285

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.643 inches  |
| Fastener Length:  |
| Between 1.128 inches and 1.158 inches   |
| Head Style:   |
| Double hexagon w/hole   |
| Head Height:  |
| Between 0.330 inches and 0.350 inches   |
| Width Between Flats:  |
| Between 0.430 inches and 0.439 inches   |
| Extended Washer Diameter:   |
| Between 0.639 inches and 0.649 inches   |
| Extended Washer Thickness:  |
| Between 0.081 inches and 0.101 inches   |
| Grip Diameter:  |
| Between 0.3735 inches and 0.3745 inches   |
| Thread Diameter:  |
| 0.375 inches  |
| Grip Length:  |
| Between 0.490 inches and 0.510 inches   |
| Thready Qty Per Inch (tpi):   |
| 24  |
| Min. Tensile Strength (psi):  |
| 220000 pounds per square inch   |
| Surface Finish:   |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Material:   |
| Nickel alloy 718  |
| Material Specification:   |
| Ams 5662 assn standard single material response                                       |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response                               |
| Thread Series Designator:   |
| Unjf  |
| Shelf Life:   |
|   |

N/a

## NSN 5306-01-338-7285

Shear Bolt - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A003b0