## NSN 5306-01-338-9334

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-338-9334

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.425 inches
Fastener Length:
Between 0.722 inches and 0.752 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Shoulder Diameter:
0.2641 inches first shoulder and 0.2651 inches first shoulder
Shoulder Length:
0.302 inches first shoulder and 0.322 inches first shoulder
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Shoulder Shape:
Round first shoulder
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6704 professional/industrial association standard
Shelf Life:
N/a

## NSN 5306-01-338-9334

Shoulder Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

