

View Online at <https://aerobasegroup.com/nsn/5306-01-338-9344>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 5.763 inches and 5.793 inches

Fastener Length:

5.172 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.701 inches and 0.721 inches

Width Between Flats:

Between 0.797 inches and 0.812 inches

Extended Washer Diameter:

Between 1.220 inches and 1.230 inches

Extended Washer Thickness:

Between 0.168 inches and 0.188 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Grip Length:

Between 4.052 inches and 4.072 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

205000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.221 inches first hole

Special Features:

Extention on end of thread 0.546 in. Min, 0.566 in. Maximum lg

Material:

Steel comp xm-13 fastener

Material Specification:

Ams 5629 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0