

View Online at <https://aerobasegroup.com/nsn/5306-01-338-9344>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 5.763 inches and 5.793 inches

**Fastener Length:**

5.172 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.701 inches and 0.721 inches

**Width Between Flats:**

Between 0.797 inches and 0.812 inches

**Extended Washer Diameter:**

Between 1.220 inches and 1.230 inches

**Extended Washer Thickness:**

Between 0.168 inches and 0.188 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 4.052 inches and 4.072 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

205000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.221 inches first hole

**Special Features:**

Extention on end of thread 0.546 in. Min, 0.566 in. Maximum lg

**Material:**

Steel comp xm-13 fastener

**Material Specification:**

Ams 5629 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0