NSN 5306-01-339-0202

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-339-0202 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.733 inches **Fastener Length:** Between 2.030 inches and 2.060 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** Between 0.089 inches and 0.109 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.302 inches and 1.322 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-339-0202

Shear Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0