

View Online at <https://aerobasegroup.com/nsn/5306-01-339-0206>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.840 inches

Fastener Length:

Between 2.200 inches and 2.230 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.470 inches and 0.490 inches

Width Between Flats:

Between 0.625 inches and 0.640 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.128 inches and 0.138 inches

Grip Diameter:

Between 0.5610 inches and 0.5615 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Bac 5861 cagec 81205 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0