

View Online at <https://aerobasegroup.com/nsn/5306-01-339-0209>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

Between 0.860 inches and 0.890 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.225 inches and 0.245 inches

**Width Between Flats:**

Between 0.297 inches and 0.312 inches

**Extended Washer Diameter:**

Between 0.465 inches and 0.475 inches

**Extended Washer Thickness:**

Between 0.032 inches and 0.052 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Product Name:**

Navy special project

**Material:**

Nickel alloy k-500

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0