## NSN 5306-01-339-0210

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-339-0210

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.643 inches
Fastener Length:
Between 1.003 inches and 1.033 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.330 inches and 0.350 inches
Width Between Flats:
Between 0.422 inches and 0.437 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Unjf

**Thread Series Designator:** 

## NSN 5306-01-339-0210

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0