## NSN 5306-01-339-3928

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-339-3928

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.343 inches
Fastener Length:
Between 2.015 inches and 2.062 inches
Head Style:
Hexagon
Head Height:
Between 0.234 inches and 0.266 inches
Width Between Flats:
Between 0.740 inches and 0.752 inches
Grip Diameter:
Between 0.4928 inches and 0.4991 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 1.678 inches and 1.698 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch  Hardness Rating:
Hardness Rating:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish:
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches grip
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Surface Finish: 32.0 microinches grip  Material:
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2, cl2 federal specification single treatment response
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2, cl2 federal specification single treatment response  Thread Series Designator:
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2, cl2 federal specification single treatment response  Thread Series Designator:  Unjf
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2, cl2 federal specification single treatment response  Thread Series Designator:  Unjf  Specification Data:
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Surface Finish:  32.0 microinches grip  Material:  Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150  Surface Treatment:  Cadmium and chromate  Surface Treatment Specification:  Qq-p-416 type 2, cl2 federal specification single treatment response  Thread Series Designator:  Unjf  Specification Data:  80205-nas464 professional/industrial association standard

--

## NSN 5306-01-339-3928

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0