NSN 5306-01-339-5006

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-339-5006

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.940 inches and 1.020 inches |
| Fastener Length: |
| Between 1.272 inches and 1.312 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.504 inches |
| Width Between Flats: |
| 0.5625 inches |
| Extended Washer Diameter: |
| 0.828 inches |
| Extended Washer Thickness: |
| 0.123 inches |
| Hole Diameter: |
| 0.055 inches |
| Grip Diameter: |
| Between 0.4985 inches and 0.4995 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| Between 0.292 inches and 0.332 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 43.0 rockwell c |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip |
| Product Name: |
| No. v. on a sigl pusic at |

Navy special project

NSN 5306-01-339-5006

Shear Bolt - Page 2 of 2

A003b0



| Material: |
|--|
| Nickel alloy 718 or cobalt comp mp-35-n |
| Material Specification: |
| Ams 5662 assn standard 1st material response or ams 5845 assn standard 2nd material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |