## NSN 5306-01-339-5925

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-339-5925

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.910 inches  |
| Fastener Length:  |
| Between 2.895 inches and 2.925 inches   |
| Head Style:   |
| Double hexagon w/hole   |
| Head Height:  |
| Between 0.470 inches and 0.490 inches   |
| Width Between Flats:  |
| Between 0.616 inches and 0.627 inches   |
| Extended Washer Diameter:   |
| Between 0.928 inches and 0.938 inches   |
| Extended Washer Thickness:  |
| Between 0.123 inches and 0.143 inches   |
| Grip Diameter:  |
| Between 0.5605 inches and 0.5615 inches   |
| Thread Diameter:  |
| 0.562 inches  |
| Grip Length:  |
| Between 1.990 inches and 2.010 inches   |
| Thready Qty Per Inch (tpi):   |
| 18  |
| Min. Tensile Strength (psi):  |
| 220000 pounds per square inch   |
| Surface Finish:   |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Material:   |
| Nickel alloy 718  |
| Material Specification:   |
| Ams 5662 assn standard single material response                                       |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response                               |
| Thread Series Designator:   |
| Unjf  |
| Shelf Life:   |
| N/a   |

## NSN 5306-01-339-5925

Shear Bolt - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV  | еа  | SU  | ıre: |

--

Demilitarization:

No

Fiig:

A003b0