

View Online at <https://aerobasegroup.com/nsn/5306-01-339-8856>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.343 inches

Fastener Length:

Between 1.763 inches and 1.793 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.676 inches and 0.690 inches

First Diameter From Head:

0.437 inches

Second Diameter From Head:

Between 0.312 inches and 0.313 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.706 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.763 inches and 1.793 inches

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Special Features:

0.363" nom grip length

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.