NSN 5306-01-340-1098

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-340-1098

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.188 inches
Fastener Length:
Between 3.548 inches and 3.578 inches
Head Style:
Spline extended washer
Head Height:
Between 0.590 inches and 0.610 inches
Extended Washer Diameter:
Between 1.384 inches and 1.394 inches
Extended Washer Thickness:
Between 0.098 inches and 0.118 inches
Grip Diameter:
Between 0.7480 inches and 0.7940 inches
Head Minor Diameter:
Between 0.904 inches and 0.912 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 2.365 inches and 2.385 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837 type 2, cl 2 military specification single treatment response

Unjf

Thread Series Designator:

NSN 5306-01-340-1098

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Shelf Life:

Mil-std (military Standard): Mil-c-8837 spec.