## NSN 5306-01-340-9848

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-340-9848 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.845 inches **Fastener Length:** Between 2.455 inches and 2.485 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Head Minor Diameter:** Between 0.485 inches and 0.500 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-340-9848

Shear Bolt - Page 2 of 2



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A003b0