

View Online at <https://aerobasegroup.com/nsn/5306-01-341-3071>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.338 inches

**Fastener Length:**

Between 0.953 inches and 0.983 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Shoulder Diameter:**

0.2485 inches first shoulder and 0.2495 inches first shoulder

**Shoulder Length:**

0.615 inches first shoulder and 0.635 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.780 inches first hole and 0.830 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard single material response

**Surface Treatment:**

Passivate headnickel grip and chromium grippassivate threads

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response headqq-c-320 cl2 federal specification single treatment response gripqq-p-35 federal specification single treatment response threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0